

ENVIRONMENTAL PRODUCT DECLARATION

READYBAC™

MODULAR CARPET TILE



Interface®

For more than four decades, Interface has consistently led the industry through design and innovation and is a world leader in environmental sustainability. We are committed to transparency and will continue to share our progress as we work to become a carbon negative company by 2040.

At Interface, we believe Life Cycle Assessment is critical for evaluating the environmental impacts of our products. The LCA-based Environmental Product Declaration is the best way to provide full disclosure of those impacts to our customers.

Interface was one of the first companies to develop EPDs for all of our products manufactured globally, and we are committed to providing this level of transparency to our customers, partners and the industry.

For more information visit www.interface.com.

ReadyBac™

This product is made to handle your high moisture projects. It features our high performance GlasBac backing with a 4 oz. attached felt cushion that adds comfort underfoot and directs moisture away from the floor's substrate, providing protection for up to 99% RH with a pH of 8.0-12.0.



ENVIRONMENTAL PRODUCT DECLARATION

Interface®

ReadyBac™



According to ISO 14025,
EN 15804, and ISO21930:2017

EPD PROGRAM AND PROGRAM OPERATOR NAME, ADDRESS, LOGO, AND WEBSITE	UL Environment 333 Pfungsten Road Northbrook, IL 60611	https://www.ul.com/ https://spot.ul.com
GENERAL PROGRAM INSTRUCTIONS AND VERSION NUMBER	General Program Instructions v.2.5 March 2020	
MANUFACTURER NAME AND ADDRESS	Interface, Inc.; Troup County, Georgia, USA	
DECLARATION NUMBER	4788873607.104.1	
DECLARED PRODUCT & FUNCTIONAL UNIT OR DECLARED UNIT	ReadyBac Modular Flooring Tile; Functional Unit of 1 square meter of floor covering	
REFERENCE PCR AND VERSION NUMBER	Part A: Life Cycle Assessment Calculation Rules and Report Requirements, (UL Environment, V3.2, 2018) and Part B: Flooring EPD Requirements (UL Environment V2.0, 2018)	
DESCRIPTION OF PRODUCT APPLICATION/USE	Interface's ReadyBac™ is made to handle high moisture projects. It features high performance GlasBac backing with a 4 ounce attached felt cushion that adds comfort underfoot and directs moisture away from the floor's substrate.	
DATE OF ISSUE	July 1, 2020	
PERIOD OF VALIDITY	5 Years	
EPD TYPE	Product-Specific	
EPD SCOPE	Cradle-to-grave	
LCA SOFTWARE & VERSION NUMBER	Gabi v. 9.2.169	
LCI DATABASE(S) & VERSION NUMBER	Gabi v. 9.2.169	
LCIA METHODOLOGY & VERSION NUMBER	TRACI 2.1	

This PCR review was conducted by:	UL Environment
	PCR Review Panel epd@ulenvironment.com
This declaration was independently verified in accordance with ISO 14025: 2006. <input type="checkbox"/> INTERNAL <input checked="" type="checkbox"/> EXTERNAL	Grant R. Martin, UL Environment
	Thomas P. Gloria, Industrial Ecology Consultants
This life cycle assessment was independently verified in accordance with ISO 14044 and the reference PCR by:	
	Thomas P. Gloria, Industrial Ecology Consultants

LIMITATIONS

Exclusions: EPDs do not indicate that any environmental or social performance benchmarks are met, and there may be impacts that they do not encompass. LCAs do not typically address the site-specific environmental impacts of raw material extraction, nor are they meant to assess human health toxicity. EPDs can complement but cannot replace tools and certifications that are designed to address these impacts and/or set performance thresholds – e.g. Type 1 certifications, health assessments and declarations, environmental impact assessments, etc.

Accuracy of Results: EPDs regularly rely on estimations of impacts; the level of accuracy in estimation of effect differs for any particular product line and reported impact.

Comparability: EPDs from different programs may not be comparable. Full conformance with a PCR allows EPD comparability only when all stages of a life cycle have been considered. However, variations and deviations are possible". Example of variations: Different LCA software and background LCI datasets may lead to differences results for upstream or downstream of the life cycle stages declared.



LIMITATIONS

Exclusions: EPDs do not indicate that any environmental or social performance benchmarks are met, and there may be impacts that they do not encompass. LCAs do not typically address the site-specific environmental impacts of raw material extraction, nor are they meant to assess human health toxicity. EPDs can complement but cannot replace tools and certifications that are designed to address these impacts and/or set performance thresholds – e.g. Type 1 certifications, health assessments and declarations, environmental impact assessments, etc.

Accuracy of Results: EPDs regularly rely on estimations of impacts; the level of accuracy in estimation of effect differs for any particular product line and reported impact.

Comparability: EPDs from different programs may not be comparable. Full conformance with a PCR allows EPD comparability only when all stages of a life cycle have been considered. However, variations and deviations are possible*. Example of variations: Different LCA software and background LCI datasets may lead to differences results for upstream or downstream of the life cycle stages declared.

1. Product Definition and Information

1.1. Description of Company/Organization

Interface, Inc. is a global flooring company specializing in carbon neutral carpet tile and resilient flooring, including luxury vinyl tile (LVT) and nora® rubber flooring. We help our customers create high-performance interior spaces that support well-being, productivity, and creativity, as well as the sustainability of the planet. Our mission, Climate Take Back™, invites you to join us as we commit to operating in a way that is restorative to the planet and creates a climate fit for life.

1.2. Product Description

Product Identification

Interface's ReadyBac™ is made to handle high moisture projects. It features high performance GlasBac backing with a 4 ounce attached felt cushion that adds comfort underfoot and directs moisture away from the floor's substrate. This Environmental Product Declaration covers all styles and patterns of modular carpet on ReadyBac™ backing with recycled Nylon yarn. The products are manufactured in Troup County, Georgia, USA. The products range in yarn weight from 407 to 1424 grams per square meter. A medium yarn weight of 678 grams per square meter is reported and the Global Warming Potential of all additional product yarn weights are reported.

Product Specification


UNSPSC code: 301617

CSI code: 09680



According to ISO 14025,
EN 15804 and ISO 21930:2017

Flow Diagram



A1-A3 measured flows include manufacturing processes, transport, and raw material inputs for each product layer and sub-layers.

Product Average

The product average with 678 grams of yarn per square meter was based on a sales weighted average.

1.3. Application

Application of product is intended for modular installation of floorcovering in commercial buildings.

1.4. Declaration of Methodological Framework

The data is retrieved from a cradle to grave LCA study. The description of study boundaries is declared in Table 11.





1.5. Technical Requirements

Technical Data

Name	Value	Unit
Yarn type	Nylon	
Primary backing type	Polyester	
Secondary backing type	ReadyBac (recycled polyester and vinyl)	
CRI rating	3.5	2.5 Moderate, 3.0 Heavy, 3.5 Severe
Total thickness	Variable	mm
Product weight*	3260	g/m ²
Surface pile thickness*	2.7	mm
Surface pile weight	678	g/m ²

* nominal values

1.6. Market Placement / Application Rules

Product considered relevant technical specifications such as ASTM E-648 and ASTM E-662. See Section 6.3 for more info.

1.7. Material Composition

Component	Material	% Mass
Yarn	Nylon	1%
	Post-consumer recycled nylon	11%
	Pre-consumer recycled nylon	8%
Primary backing	Pre & post-consumer recycled polyester	3%
Precoat backing	Vinyl acetate emulsion	4%
	Alumina trihydrate	3%
Stabilization layer	Fiberglass mat	2%
Secondary backing	Diocetyl terephthalate	8%
	Bio-based oil	1%
	Polyvinyl chloride	11%
	Pre-consumer recycled limestone	41%
	Pre-consumer polyester felt	5%





According to ISO 14025,
EN 15804 and ISO 21930:2017

1.8. Manufacturing

ReadyBac is manufactured Troup County, Georgia.

1.9. Packaging

Planks and tiles are packaged in cardboard boxes. Packaging waste should be reused or sent local cardboard recycling facilities.

1.10. Transportation

Delivery is represented as transport by truck over a distance of 500 miles (805 km).

1.11. Product Installation

Product may be installed with pressure sensitive adhesive. For full installation instructions, see the Interface Installation Guide.

1.12. Use

Conditions of use: During the reference service life of the carpet, it should be cleaned in accordance with the product warranty instructions including vacuuming and extraction cleaning. The frequency is dependent upon the expected foot traffic and local conditions.

1.13. Reference Service Life and Estimated Building Service Life

Reference service life is indicated in Table 3.

1.14. Reuse, Recycling, and Energy Recovery

The modular aspect of the product allows for easy reuse of the product. The product is intended to be recycled through Interface's ReEntry process.

1.15. Disposal

At end of life the product should be returned to Interface through Interface's ReEntry process by contacting Interface at 888-733-6873. Disposal in municipal landfill or commercial incineration facilities is permissible in accordance with local regulations.



1. Life Cycle Assessment Background Information

2.1. Functional or Declared Unit

The functional unit is one square meter of floorcovering.

Modular carpet on ReadyBac™	Value	Unit
Functional unit	1	m ²
Mass*	3.37	kg

*nominal value

2.2. System Boundary

The LCA is “cradle-to-gate with options” for one square meter of flooring. While the warranted service life is 15 years, modules **B1**, **B3**, and **B5** are not declared, so the maintenance (**B2**) is represented for one year. The system boundaries include:

- **A1** Raw material extraction and processing, and processing of recycled materials
- **A2** Transport to the factory
- **A3** Manufacturing including materials, packaging, energy, and waste disposal or recycling
- **A4** Transport to installation sites
- **A5** Installation including ancillary materials required for installation and trim-waste disposal
- **B2** Maintenance: Includes the energy for vacuuming, extraction cleaning, and the production and transport of cleaning agents. The treatment of the waste-water from extraction cleaning is included. This is for one year of use.
- **B4** Maintenance: flows related to replacement of product over Estimated Service Life (ESL) of building.
- **C2** Transport of waste to local disposal
- **C4** Disposal

2.3. Estimates and Assumptions

The datasets for materials upstream from manufacturing are a combination of information from the GaBi database and supplier provided datasets. Inventories for all materials are not available and when unavailable, conservative proxy datasets were chosen based on similarity of material.

2.4. Cut-off Criteria

As dictated by the Part A: Calculation rules for the life cycle assessment and requirements, the cut-off criteria is less than 1% for energy use and less than 1% of total mass per unit process, the sum of which shall not exceed 5% of either energy or mass. If a flow met the cut-off criteria for exclusion, yet was thought to have significant environmental impact, then it was included.





2.5. Data Sources and Quality

The datasets for materials upstream from manufacturing are a combination of information from the GaBi database version 9.2.68 in 2020 and supplier provided datasets. The data quality ranges from good to very good. The temporal quality of the data is very good with both the manufacturing specific data and the GaBi background data being from 2020.

2.6. Period under Review

The data collection and the product described are an average product manufactured in 2020.

2.7. Allocation

Where relevant, the background data incorporates some allocation such as in the power mix. There are no co-products produced in the process, so the LCA model does not include allocation. No credits were taken for recycling of production waste.



2. Life Cycle Assessment Scenarios

Table 1. Transport to the building site (A4)

Name	Value	Unit
Fuel type	Diesel	
Liters of fuel	0.00134	kg/100km
Vehicle type	Truck 34-40	tonnes
Transport distance	805	km
Capacity utilization (including empty runs, mass based)	85	%
Weight of products transported*	3.37	kg
Volume of products transported*	0.001	m ³
Capacity utilization volume factor	1	
*nominal values		

Table 2. Installation into the building (A5)

Name	Value	Unit
Ancillary materials	0.107	kg
Net freshwater consumption specified by water source and fate (amount evaporated, amount disposed to sewer)	-	m ³
Other resources	-	kg
Electricity consumption	-	kWh
Other energy carriers	-	MJ
Product loss per functional unit	0.07	kg
Waste materials at the construction site before waste processing, generated by product installation	0.16	kg
Mass of packaging waste specified by type	-	kg
Output materials resulting from on-site waste processing (specified by route; e.g. for recycling, energy recovery and/or disposal)	-	kg
Biogenic carbon contained in packaging	0.1	kg CO ₂
Direct emissions to ambient air, soil and water	-	kg
VOC content	-	µg/m ³



According to ISO 14025,
EN 15804 and ISO 21930:2017

Table 3. Reference Service Life

NAME	VALUE	UNIT
RSL	15	years

Table 4. Maintenance (B2)

NAME	VALUE	UNIT
<i>Maintenance values taken in reference to “Care and Maintenance of Commercial Carpet Conventional and Next Generation Technology: Contents of Use Phase Gate to Gate; Life Cycle Inventory Summary, Di Lu, M. Overcash and M. Realff, February 2008,” (CCACTI report).</i>		
Maintenance cycle	15	1/ RSL
Maintenance cycle	1	1/ ESL
Vacuum cleaning	365	1/year
Vacuum cleaning per RSL	5460	1/RSL
Extraction cleaning	2	1/year
Extraction cleaning per RSL	30	1/RSL
Net freshwater consumption specified by water source and fate (disposed to sewer)	1.93	kg/year
Ancillary materials (cleaning agent)	0.007	kg/year
Other resources	0.004	kg
Energy input, specified by activity, type and amount	1.6	MJ/year
Other energy carriers specified by type	-	kWh

Maintenance cycle for B2 stage is measured for 1 year per the functional unit.





According to ISO 14025,
EN 15804 and ISO 21930:2017

Table 5. Replacement (B4)

Name	Value	Unit
Reference Service Life	15	Years
Replacement cycle	4	(ESL/RSL) -1
Energy input, specified by activity, type and amount	-	kWh
Net freshwater consumption specified by water source and fate (e.g. X m3 river water evaporated, X m3 city water disposed to sewer)	-	m ³
Ancillary materials	.107	kg
Weight of replacement parts transported*	3.37	kg
Product loss per functional unit	0.07	kg
Waste materials at the construction site before waste processing, generated by product installation	0.16	kg
Direct emissions to ambient air, soil and water	-	kg
Further assumptions for scenario development, e.g. frequency and time period use	N/A	N/A
*nominal values		

Table 5. End of life (C2, C4)

NAME	VALUE	UNIT	
Assumptions for scenario development (description of deconstruction, collection, recovery, disposal method and transportation)	Assuming landfill scenario with truck transport.		
Transportation	32.0	km	
Collection process (specified by type)	Collected separately	kg	
	Collected with mixed construction waste	kg	
Recovery (specified by type)	Reuse	kg	
	Recycling	kg	
	Landfill	3.26	kg
	Incineration	kg	
	Incineration with energy recovery	kg	
	Energy conversion efficiency rate	-	
Disposal (specified by type)	Product or material for final deposition	kg	
Removals of biogenic carbon (excluding packaging)		kg CO ₂	





According to ISO 14025,
EN 15804 and ISO 21930:2017

3. Life Cycle Assessment Results

Table 6. Description of the system boundary modules (X=declared; MND=module not declared)

	PRODUCT STAGE			CONSTRUCTION PROCESS STAGE		USE STAGE							END OF LIFE STAGE				BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARY
	A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
	Raw material supply	Transport	Manufacturing	Transport from gate to site	Assembly/Install	Use	Maintenance	Repair	Replacement	Refurbishment	Building Operational Energy Use During Product Use	Building Operational Water Use During Product Use	Deconstruction	Transport	Waste processing	Disposal	Reuse, Recovery, Recycling Potential
EPD Type	X			X	X	MND	X	MND	X	MND	MND	MND	MND	X	MND	X	MND





4.1. Life Cycle Impact Assessment Results

Table 7. North American Impact Assessment Results

TRACI v2.1	A1-A3	A4	A5	B2	B4	C2	C4
GWP [kg CO ₂ eq]	4.49E+00	1.28E-01	1.17E-01	4.20E-01	1.98E+01	4.91E-03	2.13E-01
ODP [kg CFC-11 eq]	1.52E-06	3.17E-17	3.13E-08	2.12E-09	6.21E-06	1.22E-18	7.04E-16
AP [kg SO ₂ eq]	2.66E-02	6.95E-04	6.35E-04	8.44E-04	1.14E-01	2.67E-05	6.10E-04
EP [kg N eq]	3.68E-03	5.18E-05	9.15E-05	2.69E-04	1.64E-02	1.99E-06	2.80E-04
SFP [kg O ₃ eq]	3.97E-01	1.55E-02	9.19E-03	1.38E-02	1.73E+00	5.95E-04	1.00E-02
ADP _{fossil} [MJ, LHV]	1.02E+01	2.47E-01	2.64E-01	3.84E-01	4.46E+01	9.50E-03	4.27E-01

Caption	GWP 100 = global warming potential; ODP = ozone depletion potential; AP = acidification potential; EP = eutrophication potential; SFP = smog formation potential; ADP fossil= abiotic resource depletion potential of non-renewable (fossil) energy resources
---------	---

Table 8. EU Impact Assessment Results

CML v4.2	A1-A3	A4	A5	B2	B4	C2	C4
GWP 100 [kg CO ₂ eq]	4.52E+00	1.28E-01	1.19E-01	4.22E-01	2.00E+01	4.93E-03	2.16E-01
ODP [kg CFC-11 eq]	1.14E-06	3.17E-17	2.34E-08	1.95E-09	4.65E-06	1.22E-18	7.04E-16
AP [kg SO ₂ eq]	2.46E-02	5.15E-04	5.94E-04	7.76E-04	1.05E-01	1.98E-05	5.89E-04
EP [kg PO ₄ ⁻³ eq]	3.90E-03	1.29E-04	1.18E-04	1.83E-04	1.91E-02	4.96E-06	6.15E-04
POCP [kg ethene eq]	1.94E-03	-2.11E-04	5.02E-05	5.30E-05	7.35E-03	-8.11E-06	6.64E-05
ADP _{element} [kg Sb-eq]	1.04E-05	1.19E-08	2.12E-07	2.13E-07	4.27E-05	4.57E-10	4.20E-08
ADP _{fossil} [MJ, LHV]	8.20E+01	1.73E+00	2.10E+00	4.15E+00	3.57E+02	6.64E-02	3.24E+00

Caption	GWP 100 = global warming potential; ODP = depletion potential of the stratospheric ozone layer; AP = acidification potential of soil and water; EP = eutrophication potential; POCP = photochemical oxidant creation potential; ADP - elements = Abiotic depletion potential for non-fossil resources; ADP- fossil fuels = abiotic depletion potential for fossil resources
---------	---





According to ISO 14025,
EN 15804 and ISO 21930:2017

4.2. Life Cycle Inventory Results

Table 9. Resource Use

Parameter	A1-A3	A4	A5	B2	B4	C2	C4
RPRE [MJ, LHV]	2.98E+01	-	-	6.45E-01	1.19E+02	-	-
RPRM [MJ, LHV]	2.31E+01	-	-	6.19E-03	9.22E+01	-	-
NRPRE [MJ, LHV]	1.03E+00	-	-	4.08E+00	4.11E+00	-	-
NRPRM [MJ, LHV]	8.21E+01	-	-	6.25E-01	3.28E+02	-	-
SM [kg]	3.91E-01	0.00E+00	7.83E-03	0.00E+00	1.60E+00	0.00E+00	0.00E+00
RSF [MJ, LHV]	-	-	-	-	-	-	-
NRSF [MJ, LHV]	-	-	-	-	-	-	-
RE [MJ, LHV]	-	-	-	-	-	-	-
FW [m ³]	1.91E-01	2.13E-04	2.56E-04	2.18E-03	7.66E-01	4.45E-06	3.14E-05

Caption	<p>RPRE = Renewable primary resources used as energy carrier (fuel); RPRM=Renewable primary resources with energy content used as material; NRPRE= Non-renewable primary resources used as an energy carrier (fuel); NRPRM= Non-renewable primary resources with energy content used as material; SM= Secondary materials; RSF=Renewable secondary fuels; NRSF: Non-renewable secondary fuels; RE= Recovered energy;</p> <p style="text-align: center;">FW=Use of net fresh water resources</p>
---------	---





According to ISO 14025,
EN 15804 and ISO 21930:2017

Table 10. Output Flows and Waste Categories

Parameter	A1-A3	A4	A5	B2	B4	C2	C4
HWD [kg]	1.67E-03	8.03E-08	3.34E-05	1.58E-09	6.81E-03	3.08E-09	1.22E-08
NHWD [kg]	2.45E-01	2.75E-04	1.86E-01	1.86E-03	1.46E+01	1.06E-05	3.21E+00
HLRW [kg]	1.27E-06	2.98E-09	2.91E-08	4.65E-07	5.38E-06	1.14E-10	4.17E-08
ILLRW [kg]	9.73E-04	3.20E-06	2.26E-05	3.81E-04	4.16E-03	1.23E-07	4.02E-05
CRU [kg]	-	-	-	-	-	-	-
MR [kg]	-	-	-	-	-	-	-
MER [kg]	-	-	-	-	-	-	-
EE [MJ, LHV]	-	-	-	-	-	-	-

Caption	<p>HWD = hazardous waste disposed; NHWD= non-hazardous waste disposed; HLRW = high-level radioactive waste, conditioned, to final repository; ILLRW = intermediate and low-level radioactive waste, conditioned to final repository; CRU= components for reuse; MR=materials for recycling; MER=materials for energy recovery; EE= Recovered energy exported from the product system</p>
---------	--





According to ISO 14025,
EN 15804 and ISO 21930:2017

Table 11. Carbon Emissions and Removals

Parameter	A1-A3	A4	A5	B2	C2	C4
BCRP [kg CO2]	6.67E-01	0.00E+00	6.80E-06	0.00E+00	0.00E+00	1.31E-02
BCEP [kg CO2]	1.19E-02	0.00E+00	7.63E-06	0.00E+00	0.00E+00	6.24E-03
BCRK [kg CO2]	1.19E-02	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
BCEK [kg CO2]	5.21E-02	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
BCEW [kg CO2]	-	-	-	-	-	-
CCE [kg CO2]	-	-	-	-	-	-
CCR [kg CO2]	-	-	-	-	-	-
CWNR [kg CO2]	-	-	-	-	-	-

Caption	<p>BCRP [kg CO2] = Biogenic Carbon Removal from Product; BCEP [kg CO2] Biogenic Carbon Emission from Product; BCRK [kg CO2] = Biogenic Carbon Removal from Packaging; BCEK [kg CO2] = Biogenic Carbon Emission from Packaging; BCEW [kg CO2] = Biogenic Carbon Emissions from Combustion of Waste; CCE [kg CO2] = Calcination Carbon Emissions; CCR [kg CO2] = Carbonation Carbon Removal; CWNR [kg CO2] = Carbon Emissions from Combustion of Waste from Non-Renewable Sources used in Production Processes</p>
---------	--





According to ISO 14025,
EN 15804 and ISO 21930:2017

Results of the LCA - Product stage A1-A3 Global Warming Potential (GWP) for additional product yarn weights (ounces per square yard / grams per square meter)

Yarn Weight	A1-A3 Manufacturing stage
12 oz. / 407 gr.	3.86
13 oz. / 441 gr.	3.94
14 oz. / 475 gr.	4.01
15 oz. / 509 gr.	4.09
16 oz. / 542 gr.	4.17
17 oz. / 575 gr.	4.25
18 oz. / 610 gr.	4.33
19 oz. / 644 gr.	4.41
20 oz. / 678 gr.	4.49
21 oz. / 712 gr.	4.57
22 oz. / 746 gr.	4.65
23 oz. / 780 gr.	4.73
24 oz. / 814 gr.	4.81
25 oz. / 848 gr.	4.89
26 oz. / 881 gr.	4.96
27 oz. / 915 gr.	5.04
28 oz. / 949 gr.	5.12
29 oz. / 983 gr.	5.2
30 oz. / 1017 gr.	5.28
31 oz. / 1051 gr.	5.36
32 oz. / 1085 gr.	5.44
33 oz. / 1119 gr.	5.52
34 oz. / 1153 gr.	5.6
35 oz. / 1187 gr.	5.68
36 oz. / 1220 gr.	5.75
37 oz. / 1254 gr.	5.83
38 oz. / 1288 gr.	5.91
39 oz. / 1322 gr.	5.99
40 oz. / 1356 gr.	6.07
41 oz. / 1390 gr.	6.15
42 oz. / 1424 gr.	6.23

4. LCA Interpretation

The life cycle impacts of modular carpets are driven by the Product Stage and the impacts from this stage are driven by raw materials. Yarns and backing materials are the major contributors to impacts. Recycled polymers in both yarns and backings greatly reduce the impacts as compared to virgin petrochemically based materials previously used in Interface carpet manufacture.





According to ISO 14025,
EN 15804 and ISO 21930:2017

5. Additional Environmental Information

5.1 Environment and Health During Manufacturing

More information on product stewardship can be found on [Interface's sustainability website](#).

5.2 Environment and Health During Installation

All recommendations shall be utilized as indicated by SDS and installation guidelines.

5.3 Extraordinary Effects

Fire

NAME	VALUE
Radiant panel (ASTM E-648)	Class 1
Smoke density (ASTM E-662)	< 450

Water

The product's backing is impervious to water, protecting the subfloor from leaks and spills. Exposure to flooding for long periods may result in damage to the product.

Mechanical Destruction

The product is intended for commercial applications with severe wear (CRI Test method 101 Appearance Retention Rating). Performance requires proper installation according to Interface installation guidelines.

5.4 Environmental Activities and Certifications

More environmental activities and certifications can be found on [Interface's sustainability website](#).

6. References

EN 15804: EN 15804:2012-04+A1 2013: Sustainability of construction works - Environmental Product Declarations - Core rules for the product category of construction products



Interface®

ReadyBac™



According to ISO 14025,
EN 15804 and ISO 21930:2017

GaBi 9 (2019). Software-System and Databases for Life Cycle Engineering Copyright, TM. Stuttgart, Echterdingen

Interface, Inc (2020). Life Cycle Assessment of ReadyBac™.

ISO 14025: DIN EN ISO 14025:2011-10: Environmental labels and declarations - Type III environmental declarations- Principles and procedures

ISO 14040 (2006). Environmental management - Life cycle assessment – Principles and framework

ISO 14044 (2006). Environmental management - Life cycle assessment – Requirements and guidelines

ISO 21930: 2017 Sustainability in buildings and civil engineering works – Core rules for environmental product declarations of construction products and services

UL Environment General Program Instructions April 2017, version 2.1

UL Environment (2018) Product Category Rules for Building-Related Products and Services, adapted for UL Environment from the range of Environmental Product Declarations of institute Construction and Environment e. V. (IBU) Part A Calculation Rules for the Life cycle Assessment and Requirements on the Project Report

UL Environment (2020) PCR Guidance- Texts for Building-Related Products and Services. Part B: Requirements on the EPD for Floor coverings