

EPD

Environmental Product Declaration

Interface

Works Balance CQuest Bio

surface pile weight: 364 g/m²

pile material: polyamide 6, solution dyed

backing: CQuest Bio backing, heavy backing with textile bottom



GUT/Prodis ID:

FC0F82EC

**These EPD data are only valid in combination with
the environmental product declaration EPD-INT-20200182-CCC1-EN published by Institut
Bauen und Umwelt e.V. (IBU) and a GUT/Prodis license**

**This data set gives product specific LCA results
based on the calculation procedure described in the above mentioned EPD.**



Calculation method for similar Products of the EPD document

The EPD document is valid for all products with a surface pile weight lower or equal to the declared maximum pile weight of 900 g/m².


The respective declaration number is EPD-INT-20200182-CCC1-EN .

This document indicates more specific LCA results for (a) product(s) with identical material compositions and production parameters. The product(s) belong(s) to the same family of products and only differ in its/their pile weight(s).


LCA results show a linear correlation with the total pile weight, for all impact categories (IC) and all modules (A-D). It is possible to calculate specific LCA results (IC_x) for every carpet (x) within the declared group of products in relation to its total pile weight (P_x).

The total pile weight (TPW) is the sum of surface pile weight (SPW) and dead pile weight (DPW):

$$TPW = SPW + DPW$$



The surface pile weight is the technical relevant value according to EN 1307 and has to be mentioned in technical specification. As shown in the figure below alternatively to the total pile weight the surface pile weight can be used to calculate LCA results (IC_x).



Graph 1: General formula for the calculation of all impact categories IC_x.

General Information on use stages B1 to B7

LCA results indicate environmental impacts resulting from use stage B1 to B7.

For textile floor coverings only modules B1 (use) and B2 (maintenance) are taken into account. Modules B3 (repair), B4 (replacement), B5 (refurbishment), B6 (operational energy use) and B7 (operational water use) are not relevant during the service life of textile floor coverings.

Module B1 'use' includes emissions to the indoor air during the use stage. Relevant emissions only occur in the first year of life (see LCA: Calculation rules).

Module B2 'maintenance' includes cleaning procedures.

Reference service life (RSL)

The actual service life of textile floor coverings depends on a wide range of various impact factors such as the allocation of the application area to the use class, maintenance, intensity of use and most often fashion and building related aspects. Therefore, technical service life cannot be defined for textile floor coverings.

Total environmental impacts from module B2

Total environmental impacts have to be calculated by taking into account the service life of textile floor coverings. Therefore, the assumed real life (ARSL) has to be used for the calculation of total environmental impacts taking into account the expected use conditions (see RSL). Module B2 (maintenance) is depending on the service life.

Values for module B2 given in the result tables are indicated for the period of one year. They have to be multiplied by the ARSL of the textile floor covering taking into account building related aspects.


The influence of the maintenance period on the Global Warming Potential (GWP) of the whole life cycle of a textile floor covering - differentiated for 3 end-of-life scenarios - is illustrated in the graph below.

3 end-of-life scenarios:

Scenario 1: 100 % Landfill disposal

Scenario 2: 100 % Municipal waste incineration

Scenario 3: 100 % Recycling in the cement industry



Graph 2: Global Warming Potential (GWP) - aggregation of module A to module C - taking into account a maintenance period of 1 year compared to a maintenance period of 10 years - for the three declared end-of-life scenarios.

1. Information on the product Works Balance CQuest Bio

Product description

Name	Value	Unit
Type of manufacture	tufted tiles	-
Yarn type	polyamide 6, solution dyed	-
Total pile weight	558	g/m ²
Surface pile weight	364	g/m ²
Dead pile weight	194	g/m ²
Secondary backing	CQuest Bio backing, heavy backing with textile bottom	-
Product Form	planks 25 cm x 100 cm	-
Max. total carpet weight	4048	g/m ²

Base materials / Ancillary materials

Name	Value for category	Unit
Polyamide 6	13,8	%
Polyester	3,0	%
Polypropylene	1,2	%
Limestone	58,3	%
Aluminiumhydroxide	6,3	%
Ethylene vinyl acetate (EVA)	7,1	%
Wood resin	7,1	%
Glass fibre	0,8	%
Additives	2,3	%
Recycled content out of total weight	65 %	%

LCA: Declared Unit

Name	Value for category	Unit
Declared unit	1,0	m ²
Conversion factor to 1 kg	0,25	m ² /kg
Mass reference	4,0	kg/m ²

LCA: Scenarios and additional technical information

All indicated values refer to the declared functional unit

Transport to the construction site (A4)

Name	Value for category	Unit
Litres of fuel (truck, EURO 0-5 mix)	0,0095	l/100km
Transport distance	700	km
Capacity utilisation (including empty runs)	55	%

Installation in the building (A5)

Name	Value for category	Unit
Material lost	0,12	kg

Maintenance (B2)

Indication per m² and year

Name	Value for category	Unit
Maintenance cycle (wet cleaning)	1,5	1/year
Maintenance cycle (vacuum cleaning)	208	1/year
Water consumption (wet cleaning)	0,004	m ³
Cleaning agent (wet cleaning)	0,09	kg
Electricity consumption	0,314	kWh

End of Life (C1-C4)

Name	Value for category	Unit
Collected as mixed construction waste (scenario 1 and 2)	4,05	kg/m ²
Collected separately (scenario 3)	4,05	kg/m ²
Landfilling (scenario 1)	4,05	kg/m ²
Energy recovery (scenario 2)	4,05	kg/m ²
Energy recovery (scenario 3)	1,40	kg/m ²
Recycling (scenario 3)	2,65	kg/m ²

LCA: Results for Works Balance CQuest Bio

(calculated with a total pile weight of 558 g/m²)

The declared result figures in module B2 have to be multiplied by the assumed service time (in years) of the floor covering in the building considered (see chapter: 'General Information on use stages B1 to B7').

Information on un-declared modules:

Modules B3 - B7 are not relevant during the service life of the carpet and are therefore not declared.

Modules C1, C3/1, C4/2 and C4/3 cause no additional impact and are therefore not declared.

Module C2 represents the transport for scenarios 1, 2 and 3.

Description of the system boundary

(X = Included in LCA; MDN = Module not declared)

State of production	State of construction phase	State of use	End of life state	Credits and loads after life
raw material supply transport manufacturing A1 A2 A3 X X X	delivery installation A4 A5 X X	use maintenance repair replacement renewal energy use water use B1 B2 B3 B4 B5 B6 B7 X X MDN MDN MDN MDN MDN	stop of use / demolition transport waste management disposal C1 C2 C3 C4 MDN X X X	reuse, recovery and recycling potential D X

Results for the LCA - Environmental impact: 1 m² floor covering

Parameter	Unit	A1-A3	A4	A5	B1	B2	C2	C3/2	C3/3	C4/1	D/A5	D/1	D/2	D/3
GWP	[kg CO ₂ -eq]	6,64E+00	2,42E-01	5,63E-01	0,00E+00	2,92E-01	1,34E-02	4,71E+00	4,76E+00	1,17E+00	-3,52E-02	0,00E+00	-8,45E-01	-3,19E-01
ODP	[kg CFC11-eq]	2,45E-08	3,97E-17	7,34E-10	0,00E+00	1,21E-08	2,21E-18	1,84E-15	2,52E-15	8,85E-16	-4,97E-16	0,00E+00	-1,19E-14	-1,57E-15
AP	[kg SO ₂ -eq]	1,56E-02	1,02E-03	5,70E-04	0,00E+00	1,16E-03	5,65E-05	2,29E-03	2,48E-03	7,41E-04	-4,44E-05	0,00E+00	-1,06E-03	-1,16E-03
EP	[kg PO ₄ 3-eq]	1,01E-02	2,56E-04	3,27E-04	0,00E+00	3,17E-04	1,42E-05	5,49E-04	5,89E-04	7,74E-04	-5,52E-06	0,00E+00	-1,33E-04	-1,44E-04
POCP	[kg ethen-eq]	1,86E-03	-4,29E-04	4,62E-05	6,29E-05	1,48E-04	-2,38E-05	1,42E-04	8,62E-05	8,36E-05	-4,04E-06	0,00E+00	-9,70E-05	-1,15E-04
ADPE	[kg Sb-eq]	1,26E-05	2,05E-08	3,87E-07	0,00E+00	4,43E-06	1,13E-09	1,92E-07	2,02E-07	5,29E-08	-6,57E-09	0,00E+00	-1,57E-07	-1,56E-07
ADPF	[MJ]	1,42E+02	3,29E+00	4,43E+00	0,00E+00	6,76E+00	1,82E-01	2,55E+00	3,25E+00	4,07E+00	-4,93E-01	0,00E+00	-1,19E+01	-3,72E+01

GWP = Global warming potential; **ODP** = Depletion potential of the stratospheric ozone layer; **AP** = Acidification potential of land and water; **EP** = Eutrophication potential; **POCP** = Formation potential of tropospheric ozone photochemical oxidants; **ADPE** = Abiotic depletion potential for non-fossil resources; **ADPF** = Abiotic depletion potential for fossil resources

Results for the LCA - Resource use: 1 m² floor covering

Parameter	Unit	A1-A3	A4	A5	B1	B2	C2	C3/2	C3/3	C4/1	D/A5	D/1	D/2	D/3
PERE	[MJ]	3,00E+01	1,86E-01	1,67E+00	0,00E+00	1,20E+00	1,03E-02	1,37E+01	1,39E+01	2,95E-01	-1,32E-01	0,00E+00	-3,17E+00	-3,75E-01
PERM	[MJ]	1,36E+01	0,00E+00	-3,39E-01	0,00E+00	0,00E+00	0,00E+00	-1,33E+01	-1,33E+01	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
PERT	[MJ]	4,37E+01	1,86E-01	1,33E+00	0,00E+00	1,20E+00	1,03E-02	4,43E-01	6,45E-01	2,95E-01	-1,32E-01	0,00E+00	-3,17E+00	-3,75E-01
PENRE	[MJ]	1,33E+02	3,31E+00	4,99E+00	0,00E+00	7,86E+00	1,83E-01	3,01E+01	3,10E+01	4,20E+00	-6,07E-01	0,00E+00	-1,46E+01	-3,74E+01
PENRM	[MJ]	1,74E+01	0,00E+00	-2,69E-01	0,00E+00	0,00E+00	0,00E+00	-2,73E+01	-2,73E+01	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
PENRT	[MJ]	1,51E+02	3,31E+00	4,72E+00	0,00E+00	7,86E+00	1,83E-01	2,83E+00	3,68E+00	4,20E+00	-6,07E-01	0,00E+00	-1,46E+01	-3,74E+01
SM	[kg]	2,64E+00	0,00E+00	7,92E-02	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	2,00E-01
RSF	[MJ]	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
NRSF	[MJ]	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
FW	[m ³]	3,31E-01	2,15E-04	1,04E-02	0,00E+00	4,27E-03	1,19E-05	1,41E-02	1,43E-02	5,15E-05	-1,53E-04	0,00E+00	-3,67E-03	-3,26E-03

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; **PERM** = Use of renewable primary energy resources used as raw materials; **PERT** = Total use of renewable primary energy resources; **PENRE** = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; **PENRM** = Use of non-renewable primary energy resources used as raw materials; **PENRT** = Total use of non-renewable primary energy resources; **SM** = Use of secondary material; **RSF** = Use of renewable secondary fuels; **NRSF** = Use of non-renewable secondary fuels; **FW** = Use of net fresh water

Results for the LCA - Output flows and waste categories: 1 m² floor covering

Parameter	Unit	A1-A3	A4	A5	B1	B2	C2	C3/2	C3/3	C4/1	D/A5	D/1	D/2	D/3
HWD	[kg]	3,80E-07	1,54E-07	1,69E-08	0,00E+00	9,63E-10	8,52E-09	1,68E-08	3,83E-08	1,53E-08	-2,42E-10	0,00E+00	-5,81E-09	-8,31E-09
NHWD	[kg]	2,41E-01	5,06E-04	4,75E-02	0,00E+00	5,63E-03	2,80E-05	1,34E+00	1,34E+00	4,03E+00	-2,80E-04	0,00E+00	-6,72E-03	-1,22E-01
RWD	[kg]	3,37E-03	4,09E-06	1,05E-04	0,00E+00	3,38E-04	2,27E-07	1,09E-04	1,70E-04	5,07E-05	-4,52E-05	0,00E+00	-1,08E-03	-9,64E-05
CRU	[kg]	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
MFR	[kg]	0,00E+00	0,00E+00	1,21E-01	0,00E+00	0,00E+00	0,00E+00	0,00E+00	1,52E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
MER	[kg]	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
EEE	[MJ]	0,00E+00	0,00E+00	1,45E-01	0,00E+00	0,00E+00	0,00E+00	3,41E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
EET	[MJ]	0,00E+00	0,00E+00	2,76E-01	0,00E+00	0,00E+00	0,00E+00	6,69E+00	4,99E+01	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00

HWD = Hazardous waste disposed; **NHWD** = Non-hazardous waste disposed; **RWD** = Radioactive waste disposed; **CRU** = Components for re-use; **MFR** = Materials for recycling; **MER** = Materials for energy recovery; **EEE** = Exported electrical energy; **EET** = Exported thermal energy