



**Installation Method**



Non Directional

Interface European Manufacturing BV reserve the right to change or modify specifications.

**Product** Straightforward II **Colour** 4268018 Crystal

**Product Specifications**

Product Number	4268
Product Construction	Microtuft Patterned Level Loop Pile
Yarn System	100% Solution Dyed Nylon, derived from biomass
Standard Backing	CQuest™Bio
Size – Packaging	50cm x 50cm
Pile Yarn Weight	420 g/m <sup>2</sup> ± 5%
Total Weight	4074 g/m <sup>2</sup> ± 5%
Total Thickness	4.8 mm ± 0.5 mm
Gauge – Ends per 10 cm	5/64 - 50.4
Tufts per m <sup>2</sup>	186,480/m <sup>2</sup> ±5%

**Performance Specifications**

Wear Classification	EN 1307 33 Heavy Contract					
Castor Chair Rating	≥2.4 (EN 985) Continuous Use					
Flammability	(EN ISO 9239-1) Euroclass Cfl-s1 (EN 13501-1)					
Light Fastness	≥7 (ISO 105-B02)					
Light Reflectance Value (LRV)	LRV – L value			LRV – Y value		
	32.9			7.5		
Dimensional Stability	≤0.2% (ISO 2551/EN 986)					
Impact Sound Insulation ΔL <sub>w</sub> EN ISO 10140-3	16 dB					
Rating of Sound Absorption (α <sub>w</sub> ) EN ISO 11654	0.15					
Sound Absorption (α <sub>s</sub> ) EN ISO 354	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz
	0.01	0.01	0.06	0.14	0.25	0.33

**Environmental Specifications**

Total Recycled Content	71.7%
Pre-Consumer (Total)	71.7%
Post-Consumer (Total)	0%
Yarn Recycled Content	0%
Pre-Consumer (Yarn)	0%
Post-Consumer (Yarn)	0%
Total Bio Based Content	12%
Total Recycled & Bio Based Content	83.7%
Indoor Air Quality	GUT Prodis ID AAB3EAE3 French A+ <a href="#">Compliant with LEED EQ 4.3 credit</a> <a href="#">GLP 100209</a> <a href="#">M1 Emission Certification -CQB</a>
Potential Green Building Contribution	
BREEAM (UK/International)	<a href="#">View potential BREEAM contribution</a>
LEED (US/International)	<a href="#">View Potential Leed Contribution</a>
HQE (France)	<a href="#">View Potential HQE Contribution</a>
DGNB (Germany)	<a href="#">View Potential DGNB Contribution</a>
Environmental Product Declaration	In Progress

Full Life Cycle Carbon Footprint	According to EPD or EPD calculation method
Full Life Cycle Carbon	Certified Carbon Neutral Floors™
<b>Installation Impacts</b>	
Installation Waste	In a typical installation (rectangular building, installed before walls) using the installation method below:  Non-directional – 1-2%  For reference: 2 m wide broadloom typically generates 7-10% installation waste
TacTiles®	Optimised for glue-free installation with TacTiles® connectors with virtually zero VOCs
<b>End of Life Options</b>	
Waste to Energy	Can be incinerated in appropriate waste to energy plant.
Recycling	Can be returned through the Interface ReEntry scheme and be reused as raw material in new carpet tiles.
ReUse	Can be cleaned and reused in a non-critical location to extend its useful life.

**Technical Information**

Installation	<a href="#">See recommended Interface installation guidelines</a>
Maintenance	<a href="#">See recommended Interface maintenance guidelines</a>
Warranty	15 years
Manufacturing Location	<a href="#">ISO 9001, 14001 &amp; 45001 Certified Facilities in Europe</a>

**Performance Qualifications**

16 dB   0.15   ≥7   0.033 m² K/W   ≥2.4

**Certifications**

EN 14041  
CE  
DOP : 1037-127348  
textile floor covering  
EN 1307

AAB3EAE3  
www.pro-dis.info

ÉMISSIONS DANS L'AIR INTÉRIEUR  
A+