



**Installation Method**



Monolithic

Interface European Manufacturing BV reserve the right to change or modify specifications.

**Collection** Touch & Tones II **Product** Touch & Tones II 102 **Colour** 4175079 Forest

**Product Specifications**

Product Number	4175
Product Construction	Tufted Plain Textured Loop Pile
Yarn System	100% Recycled Nylon
Standard Backing	CQuest™Bio
Optional Backing(s) <a href="#">(Learn more)</a>	ReCushion Bac®
Size – Packaging	50cm x 50cm
Pile Yarn Weight	925 g/m <sup>2</sup> ± 5%
Total Weight	4154 g/m <sup>2</sup> ± 5%
Pile Height	4.9 mm +15% / - 10%
Total Thickness	8.5 mm ± 0.5 mm
Gauge – Ends per 10 cm	1/10 - 39.4
Tufts per m <sup>2</sup>	110,320/m <sup>2</sup> ±5%

**Performance Specifications**

Wear Classification	EN 1307 33 Heavy Contract					
Castor Chair Rating	≥2.4 (EN 985) Continuous Use					
Flammability	(EN ISO 9239-1) Euroclass Cfl-s1 (EN 13501-1)					
Light Fastness	≥5 (ISO 105-B02)					
Light Reflectance Value (LRV)	LRV – L value			LRV – Y value		
	28.98			5.83		
Dimensional Stability	≤0.2% (ISO 2551/EN 986)					
Impact Sound Insulation ΔL <sub>w</sub> EN ISO 10140-3	27 dB					
Rating of Sound Absorption (α <sub>w</sub> ) EN ISO 11654	0.20					
Sound Absorption (α <sub>s</sub> ) EN ISO 354	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz
	-0.02	0.06	0.08	0.20	0.34	0.40

**Environmental Specifications**

Total Recycled Content	82.4%
Pre-Consumer (Total)	71.3%
Post-Consumer (Total)	11.1%
Yarn Recycled Content	100%
Pre-Consumer (Yarn)	50%
Post-Consumer (Yarn)	50%
Total Bio Based Content	9.1%
Total Recycled & Bio Based Content	91.5%
Indoor Air Quality	GUT Prodis ID 1D5ABBA8 <a href="#">GLP 100254 PD</a> French A+ <a href="#">M1 Emission Certification -CQB</a> <a href="#">GUI Standard</a>
Potential Green Building Contribution	
BREEAM (UK/International)	<a href="#">View potential BREEAM contribution</a>
LEED (US/International)	<a href="#">View Potential Leed Contribution</a>
HQE (France)	<a href="#">View Potential HQE Contribution</a>
DGNB (Germany)	<a href="#">View Potential DGNB Contribution</a>
Environmental Product Declaration	<a href="#">EPD_TouchandTonesII102_CQB</a>

Full Life Cycle Carbon Footprint	According to EPD or EPD calculation method
Embodied Carbon (Cradle to Gate)	4.18 kg CO <sub>2</sub> eq./m <sup>2</sup>
Full Life Cycle Carbon	Certified Carbon Neutral Floors™
<b>Installation Impacts</b>	
Installation Waste	In a typical installation (rectangular building, installed before walls) using the installation method below:  Monolithic – 3-4%  For reference: 2 m wide broadloom typically generates 7-10% installation waste
TacTiles®	Optimised for glue-free installation with TacTiles® connectors with virtually zero VOCs
<b>End of Life Options</b>	
ReUse	Can be cleaned and reused in a non-critical location to extend its useful life.
Recycling	Can be returned through the Interface ReEntry scheme and be reused as raw material in new carpet tiles.
Waste to Energy	Can be incinerated in appropriate waste to energy plant.

**Technical Information**

Installation	<a href="#">See recommended Interface installation guidelines</a>
Maintenance	<a href="#">See recommended Interface maintenance guidelines</a>
Warranty	15 years
Manufacturing Location	<a href="#">ISO 9001, 14001 &amp; 45001 Certified Facilities in Europe</a>

**Performance Qualifications**

27 dB   0.20   ≥5   0.083 m<sup>2</sup> K/W   ≥2.4

**Certifications**

EN 14041  
CE  
DOP : 1037-128288  
textile floor covering  
EN 1307

RED A1  
1D5ABBA8  
www.pro-dis.info

GREENGUARD  
EMITTING LOW VOC'S  
GREENGUARD  
CERTIFIED  
GREENGUARD  
CERTIFIED

ÉMISSIONS DANS L'AIR INTÉRIEUR  
A+  
A+ A B C

ISO 9001  
CERTIFIED