



#### Installation Method



Ashlar Herringbone

Interface European Manufacturing BV reserve the right to change or modify specifications.

Collection Works Product Works Fluid Colour 4285006 Taupe

#### Product Specifications

Product Number	4285
Product Construction	Tufted Patterned Structured Loop Pile
Yarn System	100% Solution Dyed Nylon
Standard Backing	CQuest™Bio
Optional Backing(s) <a href="#">(Learn more)</a>	CQuestBio SONE, CQuestBio SONE+, ReCushion Bac®
Size – Packaging	25cm x 100cm
Pile Yarn Weight	596 g/m <sup>2</sup> ± 5%
Effective Pile Yarn Weight	391 g/m <sup>2</sup> ± 10%
Total Weight	3884 g/m <sup>2</sup> ± 5%
Pile Height	3.7 mm +15% / - 10%
Total Thickness	7.1 mm ± 0.5 mm
Gauge – Ends per 10 cm	1/12 - 47.2
Tufts per m <sup>2</sup>	194,120/m <sup>2</sup> ± 5%

#### Performance Specifications

Wear Classification	EN 1307 33 Heavy Contract					
Castor Chair Rating	≥2.4 (EN 985) Continuous Use					
Flammability	(EN ISO 9239-1) Euroclass Bfl-s1 (EN 13501-1)					
Light Fastness	≥7 (ISO 105-B02)					
Light Reflectance Value (LRV)	LRV – L value			LRV – Y value		
	47.77			16.61		
Dimensional Stability	≤0.2% (ISO 2551/EN 986)					
Impact Sound Insulation ΔL <sub>w</sub> EN ISO 10140-3	23 dB					
Rating of Sound Absorption (α <sub>w</sub> ) EN ISO 11654	0.20					
Sound Absorption (α <sub>s</sub> ) EN ISO 354	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz
	0.04	0.02	0.08	0.19	0.34	0.43

#### Environmental Specifications

Total Recycled Content	62.8%
Pre-Consumer (Total)	62.8%
Post-Consumer (Total)	0%
Yarn Recycled Content	0%
Pre-Consumer (Yarn)	0%
Post-Consumer (Yarn)	0%
Total Bio Based Content	9.75%
Total Recycled & Bio Based Content	72.55%
Indoor Air Quality	GUT Prodis ID C876E9FB
	French A+
	<a href="#">GLP 100209</a>
	<a href="#">M1 Emission Certification -CQB</a> <a href="#">GUI Standard</a>
Potential Green Building Contribution	
BREEAM (UK/International)	<a href="#">No</a>
LEED (US/International)	<a href="#">View Potential Leed Contribution</a>
HQE (France)	<a href="#">View Potential HQE Contribution</a>
DGNB (Germany)	<a href="#">View Potential DGNB Contribution</a>
Environmental Product Declaration	<a href="#">EPD_WorksFluid_CQB</a>

Full Life Cycle Carbon Footprint	According to EPD or EPD calculation method
Embodied Carbon (Cradle to Gate)	7.01 kg CO <sub>2</sub> eq./m <sup>2</sup>
Full Life Cycle Carbon	Certified Carbon Neutral Floors™
<b>Installation Impacts</b>	
Installation Waste	In a typical installation (rectangular building, installed before walls) using the installation method below:  Herringbone – 3-5%  Ashlar – 3-5 %  For reference: 2 m wide broadloom typically generates 7-10% installation waste
TacTiles®	Optimised for glue-free installation with TacTiles® connectors with virtually zero VOCs
<b>End of Life Options</b>	
Recycling	Can be returned through the Interface ReEntry scheme and be reused as raw material in new carpet tiles.
ReUse	Can be cleaned and reused in a non-critical location to extend its useful life.
Waste to Energy	Can be incinerated in appropriate waste to energy plant.

**Technical Information**

Warranty	<a href="#">15 years</a>
Manufacturing Location	<a href="#">ISO 9001, 14001 &amp; 45001 Certified Facilities in Europe</a>

**Performance Qualifications**

23 dB   0.20   ≥7   0.07   ≥2.4  
m<sup>2</sup> K/W

**Certifications**

EN 14041  
CE  
DOP : 1037-127358  
textile floor covering  
EN 1307

RED NR  
C876E9FB  
www.pro-dis.info

GUT  
GREEN BUILDING  
CERTIFICATION  
UNIVERSITY OF  
SOUTH ALABAMA

ÉMISSIONS DANS L'AIR INTÉRIEUR  
A+  
A+ A B C