



**Installation Method**



Ashlar Herringbone

Interface European Manufacturing BV reserve the right to change or modify specifications.

**Product** Brushed Lines **Colour** A01604 Galena

**Product Specifications**

Product Number	A016
Product Construction	High Performance Luxury Vinyl Tile Contains 39% Pre-Consumer Recycled Content
Finish	Ceramor™ - UV Stabilised Ceramic Bead Coating
Wear Layer Thickness	(EN ISO 24340) 0.55 mm
Total Thickness	(EN ISO 24346) 4.5mm
Total Weight	(EN ISO 23997) 6880 g/m <sup>2</sup>
Size – Packaging	25cm x 1m
Backing	Sound Choice™ Acoustic Backing

**Performance Specifications**

Wear Classification	EN ISO 10874 33 Heavy Commercial / 42 General Light Industrial	
CE Declaration Of Performance	<a href="#">DOP PBRG-AHCK3R</a>	
UKCA Declaration of Performance	<a href="#">DOP PBRG-AHCK3R</a>	
Castor Chair Rating	(ISO 4918 / EN425) Pass	
Flammability	(EN ISO 9239-1) Euroclass Bfl-s1 (EN 13501-1)	
Light Fastness	≥7 (ISO 105-B02)	
Light Reflectance Value (LRV)	LRV – L value	LRV – Y value
	55.99	23.9
Dimensional Stability	(ISO 23999) ≤ 0.25%	
Curling	(ISO 23999) ≤ 2 mm	
Flexibility	(EN ISO 24344) Method A - Pass.	
Abrasion Resistance	(EN 660-2) Group T	
Residual Indentation	mm(EN ISO 24343-1) ≤ 0.2	
Determination of Anti-Slip	(DIN 51130) R10	
Chemical Resistance	(EN ISO 26987) Very Good	
Impact Sound Insulation ΔL <sub>w</sub> EN ISO 10140-3	16 dB	

**Environmental Specifications**

Total Recycled Content	39%
Indoor Air Quality	French A+ <a href="#">Indoor Air Comfort GOLD®</a> <a href="#">M1 Emission Certification - LVT</a> <a href="#">LVT Greenguard Gold</a>
Potential Green Building Contribution	
Environmental Product Declaration	<a href="#">MR-ULE-EPD-INF-20170001-EN</a>
Full Life Cycle Carbon Footprint	According to EPD or EPD calculation method
Embodied Carbon (Cradle to Gate)	9.2 kg CO <sub>2</sub> eq./m <sup>2</sup>
Full Life Cycle Carbon	Certified Carbon Neutral Floors™
Installation Impacts	
TacTiles®	No
End of Life Options	
Fully Recyclable	Can be recycled into carpet tile backing.
ReUse	Can be cleaned and reused in a non-critical location to extend its useful life.
Material Composition	Free of Ortho Phthalates

**Technical Information**

Installation	<a href="#">See recommended LVT installation guidelines</a>
Maintenance	<a href="#">See recommended LVT maintenance guidelines</a>
Warranty	<a href="#">15 years LVT</a>

**Performance Qualifications**



Certifications

	
17	
Interface European Manufacturing B.V. Industrielaan 15 3925 BD Scherpenzeel The Netherlands	
DOP PBRG – AHCK3R	
EN 14041:2004 Notified Body - 0493	
Resilient floor covering for internal use.	
Classification	Class 33/42 (EN ISO 10874)
Reaction to fire	Class Bfl-s1 (see EN 14041, clause 4.1)
Slip resistance	Class DS (See EN 14041, clause 4.5)
Formaldehyde	E1 (see EN 14041, clause 4.3)
Anti-static	<2.0kV (See EN14041, clause 4.6.1)
<a href="http://www.interface.com/lv-emea">www.interface.com/lv-emea</a>	

	
21	
Interface European Manufacturing B.V. Industrielaan 15 3925 BD Scherpenzeel The Netherlands	
DOP PBRG – AHCK3R	
EN 14041:2004 Approved Body - 0321	
Resilient floor covering for internal use.	
Classification	Class 33/42 (EN ISO 10874)
Reaction to fire	Class Bfl-s1 (see EN 14041, clause 4.1)
Slip resistance	Class DS (See EN 14041, clause 4.5)
Formaldehyde	E1 (see EN 14041, clause 4.3)
Anti-static	<2.0kV (See EN14041, clause 4.6.1)
<a href="http://www.interface.com/lv-emea">www.interface.com/lv-emea</a>	

