



#### Installation Method



Non Directional

Interface European Manufacturing BV reserve the right to change or modify specifications.

**Product** Iridescence **Colour** A01912 Blossom

#### Product Specifications

Product Number	A019
Product Construction	High Performance Luxury Vinyl Tile Contains 39% Pre-Consumer Recycled Content
Finish	Ceramor™ - UV Stabilised Ceramic Bead Coating
Wear Layer Thickness	(EN ISO 24340) 0.55 mm
Total Thickness	(EN ISO 24346) 4.5mm
Total Weight	(EN ISO 23997) 6880 g/m <sup>2</sup>
Size – Packaging	50cm x 50cm
Backing	Sound Choice™ Acoustic Backing

#### Performance Specifications

Wear Classification	EN ISO 10874 33 Heavy Commercial / 42 General Light Industrial	
CE Declaration Of Performance	<a href="#">DOP PBRG-AHCK3R</a>	
UKCA Declaration of Performance	<a href="#">DOP PBRG-AHCK3R</a>	
Castor Chair Rating	(ISO 4918 / EN425) Pass	
Flammability	(EN ISO 9239-1) Euroclass Bfl-s1 (EN 13501-1)	
Light Fastness	≥7 (ISO 105-B02)	
Light Reflectance Value (LRV)	LRV – L value	LRV – Y value
	59.59	27.67
Dimensional Stability	(ISO 23999) ≤ 0.25%	
Curling	(ISO 23999) ≤ 2 mm	
Flexibility	(EN ISO 24344) Method A - Pass.	
Abrasion Resistance	(EN 660-2) Group T	
Residual Indentation	mm(EN ISO 24343-1) ≤ 0.2	
Determination of Anti-Slip	(DIN 51130) R10	
Chemical Resistance	(EN ISO 26987) Very Good	
Impact Sound Insulation ΔL <sub>w</sub> EN ISO 10140-3	16 dB	

#### Environmental Specifications

Total Recycled Content	39%
Indoor Air Quality	<a href="#">Indoor Air Comfort GOLD®</a> French A+ <a href="#">M1 Emission Certification - LVT</a> <a href="#">LVT Greenguard Gold</a>
Potential Green Building Contribution	
BREEAM (UK/International)	<a href="#">View potential BREEAM contribution</a>
LEED (US/International)	<a href="#">View Potential Leed Contribution</a>
DGNB (Germany)	<a href="#">View Potential DGNB Contribution</a>
Environmental Product Declaration	<a href="#">MR-ULE-EPD-INF-20170001-EN</a>
Full Life Cycle Carbon Footprint	According to EPD or EPD calculation method
Embodied Carbon (Cradle to Gate)	9.2 kg CO <sub>2</sub> eq./m <sup>2</sup>
Full Life Cycle Carbon	Certified Carbon Neutral Floors™
Installation Impacts	
TacTiles®	Can be installed with glue-free TacTiles® for PVC up to 50 m2, for virtually zero VOCs.
End of Life Options	
Fully Recyclable	Can be recycled into carpet tile backing.
ReUse	Can be cleaned and reused in a non-critical location to extend its useful life.
Material Composition	Free of Ortho Phthalates
<b>Technical Information</b>	
Installation	<a href="#">See recommended LVT installation guidelines</a>
Maintenance	<a href="#">See recommended LVT maintenance guidelines</a>
Warranty	<a href="#">15 years LVT</a>

#### Performance Qualifications



Certifications

**CE**

---

17

---

Interface European Manufacturing B.V.  
Industrielaan 15  
3925 BD  
Scherpenzeel  
The Netherlands

---

DOP PBRG – AHCK3R

---

EN 14041:2004  
Notified Body - 0493

---

Resilient floor covering for internal use.

Classification	Class 33/42 (EN ISO 10874)
Reaction to fire	Class Bfl-s1 (see EN 14041, clause 4.1)
Slip resistance	Class DS (See EN 14041, clause 4.5)
Formaldehyde	E1 (see EN 14041, clause 4.3)
Anti-static	<2.0kV (See EN14041, clause 4.6.1)

---

[www.interface.com/lt-emea](http://www.interface.com/lt-emea)

**UK  
CA**

---

21

---

Interface European Manufacturing B.V.  
Industrielaan 15  
3925 BD  
Scherpenzeel  
The Netherlands

---

DOP PBRG – AHCK3R

---

EN 14041:2004  
Approved Body - 0321

---

Resilient floor covering for internal use.

Classification	Class 33/42 (EN ISO 10874)
Reaction to fire	Class Bfl-s1 (see EN 14041, clause 4.1)
Slip resistance	Class DS (See EN 14041, clause 4.5)
Formaldehyde	E1 (see EN 14041, clause 4.3)
Anti-static	<2.0kV (See EN14041, clause 4.6.1)

---

[www.interface.com/lt-emea](http://www.interface.com/lt-emea)

